

JBCRD POWER RELAY

(RoHS 2011/65/EU & ELV 2000/53/EC 対応品)

マイクロソケット			Rated Voltage 12VDC 24VDC JBC Part No J01-CDE-1K J01-CDE-2K Resistive lode NO:35A NO:15A NC:20A NC:10A Contact circuit configuration 1c 1c Coil surge measures Diode Diode Socket JSK-015、115 JSK-015、115 Product Number	12VDC 24VDC J01-CDE-1K J01-CDE-2K NO:35A NO:15A NC:20A NC:10A 1c 1c Diode Diode JSK-015、115 JSK-015、115
			Rated Voltage 12VDC 24VDC JBC Part No J01-CRE-1K J01-CRE-2K Resistive lode NO:35A NO:15A NC:20A NC:10A Contact circuit configuration 1c 1c Coil surge measures Resistance Resistance Socket JSK-015、115 JSK-015、115 Product Number	12VDC 24VDC J01-CRE-1K J01-CRE-2K NO:35A NO:15A NC:20A NC:10A 1c 1c Resistance Resistance JSK-015、115 JSK-015、115
			Rated Voltage 12VDC 24VDC JBC Part No J01-ARE-1 J01-ARE-2 Resistive lode NO:35A NO:15A - - Contact circuit configuration 1a 1a Coil surge measures Resistance Resistance Socket JSK-015、115 JSK-015、115 Product Number J01-1AR112VDC J01-1AR124VDC	12VDC 24VDC J01-ARE-1 J01-ARE-2 NO:35A NO:15A - - 1a 1a Resistance Resistance JSK-015、115 JSK-015、115
マイクロソケット			Rated Voltage 12VDC JBC Part No J01-CD-1 Resistive lode NO:35A NC:20A Contact circuit configuration 1c Coil surge measures Diode Socket JSK-015、115 Product Number J01-CD-1	
			Rated Voltage 12VDC 24VDC JBC Part No J01-CDE-1 J01-CDE-2 Resistive lode NO:35A NO:15A NC:20A NC:10A Contact circuit configuration 1c 1c Coil surge measures Diode Diode Socket JSK-015、115 JSK-015、115 Product Number J01-1CS-D112VDC J01-1CS-D124VDC	12VDC 24VDC J01-CDE-1 J01-CDE-2 NO:35A NO:15A NC:20A NC:10A 1c 1c Diode Diode JSK-015、115 JSK-015、115
			Rated Voltage 12VDC 24VDC JBC Part No J01-CRE-1 J01-CRE-2 Resistive lode NO:35A NO:15A NC:20A NC:10A Contact circuit configuration 1c 1c Coil surge measures Resistance Resistance Socket JSK-015、115 JSK-015、115 Product Number J01-1CR112VDC J01-1CR124VDC	12VDC 24VDC J01-CRE-1 J01-CRE-2 NO:35A NO:15A NC:20A NC:10A 1c 1c Resistance Resistance JSK-015、115 JSK-015、115
マイクロソケット			Rated Voltage 12VDC 24VDC JBC Part No J01-AR-1S J01-AR-2S Resistive lode NO:35A NO:15A - - Contact circuit configuration 1a 1a Coil surge measures Resistance Resistance Socket JSK-015、115 JSK-015、115 Product Number J01-1ACFR1 12VDC J01-1ACFR1 24VDC	12VDC 24VDC J01-AR-1S J01-AR-2S NO:35A NO:15A - - 1a 1a Resistance Resistance JSK-015、115 JSK-015、115
			Rated Voltage 12VDC 24VDC JBC Part No J01-CR-1S J01-CR-2S Resistive lode NO:35A NO:15A NC:20A NC:10A Contact circuit configuration 1c 1c Coil surge measures Resistance Resistance Socket JSK-015、115 JSK-015、115 Product Number J01-1CCFR1 12VDC J01-1CCFR1 24VDC	12VDC 24VDC J01-CR-1S J01-CR-2S NO:35A NO:15A NC:20A NC:10A 1c 1c Resistance Resistance JSK-015、115 JSK-015、115

JBCRD POWER RELAY

(RoHS 2011/65/EU & ELV 2000/53/EC 対応品)

マイクロソリレー			Rated Voltage 12VDC JBC Part No J11-ARE-1 Resistive lode NO:25A Contact circuit configuration - Coil surge measures 1a Socket JSK-015、115 Product Number J11-ARE-1	
			Rated Voltage 12VDC JBC Part No J11-ADE-1 Resistive lode NO:25A Contact circuit configuration 1a Coil surge measures Diode Socket JSK-015、115 Product Number J11-ADE-1	
			Rated Voltage 12VDC JBC Part No J03-CDE-1 Resistive lode NO:35A Contact circuit configuration 1c Coil surge measures Diode Socket 設定無し Product Number 301-1C-S-D1 12VDC	24VDC J03-CDE-2 NO:15A NC:10A 1c Diode 設定無し 301-1C-S-D1 24VDC
ミニチュアソリレー B種			Rated Voltage 12VDC JBC Part No J04-AR-1SK Resistive lode NO:30A Contact circuit configuration 1a Coil surge measures Resistance Socket JSK-044 Product Number J04-C1R112VDC	24VDC J04-AR-2SK NO:15A 1a Resistance JSK-044 J04-C1R124VDC
			Rated Voltage 12VDC JBC Part No J04-AD-1SK Resistive lode NO:30A Contact circuit configuration 1a Coil surge measures Diode Socket JSK-044 Product Number J04-C1D1 12VDC	24VDC J04-AD-2SK NO:15A 1a Diode JSK-044 J04-C1D124VDC
ミニソリレー			Rated Voltage 12VDC JBC Part No NEW Resistive lode NEW Contact circuit configuration NEW Coil surge measures Diode Socket JSK-065 Product Number JE6-CDE-2K	24VDC JE6-CDE-2K NO:20A NC:15A 1c Diode JSK-065 JE6-CDE-2K
			Rated Voltage 12VDC JBC Part No J06-CRE-1K Resistive lode NO:50A Contact circuit configuration 1c Coil surge measures Resistance Socket JSK-065 Product Number J06-1CS1S 12VDC	24VDC J06-CRE-2K NO:20A NC:15A 1c Resistance JSK-065 J06-1CS1S 24VDC
			Rated Voltage 12VDC JBC Part No J06-CDE-1K Resistive lode NO:50A Contact circuit configuration 1c Coil surge measures Diode Socket JSK-065 Product Number J06-1CS1S-D1 12VDC	24VDC J06-CDE-2K NO:20A NC:15A 1c Diode JSK-065 J06-1CS1S-D1 24VDC

JBCRD POWER RELAY

(RoHS 2011/65/EU & ELV 2000/53/EC 対応品)

ミニISOリレー	<p>STOCK ONLY</p> <p>Dimensions: $\phi 6.5$, 15.2, 25, 25.8, 30</p>	<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J06-WRE-1K</p> <p>NO:30A NC:30A</p> <p>2a</p> <p>Resistance</p> <p>JSK-065</p> <p>J06-2AS1S 12VDC</p>	<p>24VDC</p> <p>J06-WRE-2K</p> <p>NO:10A NC:10A</p> <p>2a</p> <p>Resistance</p> <p>JSK-065</p> <p>J06-2AS1S 24VDC</p>
		<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J06-WDE-1K</p> <p>NO:30A NC:30A</p> <p>2a</p> <p>Diode</p> <p>JSK-065</p> <p>J06-2AS1S-D1 12VDC</p>	<p>24VDC</p> <p>J06-WDE-2K</p> <p>NO:10A NC:10A</p> <p>2a</p> <p>Diode</p> <p>JSK-065</p> <p>J06-2AS1S-D1 24VDC</p>
ミニISOリレー	<p>Dimensions: 25.8, 25, 25.8</p>	<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J06-CRE-1</p> <p>NO:50A NC:30A</p> <p>1c</p> <p>Resistance</p> <p>JSK-065</p> <p>J06-1CS 12VDC</p>	<p>24VDC</p> <p>J06-CRE-2</p> <p>NO:20A NC:15A</p> <p>1c</p> <p>Resistance</p> <p>JSK-065</p> <p>J06-1CS 24VDC</p>
		<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J06-CDE-1</p> <p>NO:50A NC:30A</p> <p>1c</p> <p>Diode</p> <p>JSK-065</p> <p>J06-1CS-D1 12VDC</p>	<p>STOCK ONLY</p>
ミニISOリレー 高容量	<p>Dimensions: $\phi 6.5$, 15.2, 25, 25.8, 30, 40</p>	<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J07-ARE-1K</p> <p>NO:70A</p> <p>-</p> <p>1a</p> <p>Resistance</p> <p>JSK-074</p> <p>J07-1AS1S 12VDC</p>	<p>24VDC</p> <p>J07-ARE-2K</p> <p>NO:25A</p> <p>-</p> <p>1a</p> <p>Resistance</p> <p>JSK-074</p> <p>J07-1AS1S 24VDC</p>
		<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J07-ADE-1K</p> <p>NO:70A</p> <p>-</p> <p>1a</p> <p>Diode</p> <p>JSK-074</p> <p>J07-ADE-1K</p>	
ミニISO280リレー	<p>Dimensions: 25.8, 25, 25.8</p>	<p>Wiring Diagram</p>	<p>Rated Voltage</p> <p>JBC Part No</p> <p>Resistive lode</p> <p>Contact circuit configuration</p> <p>Coil surge measures</p> <p>Socket</p> <p>Product Number</p>	<p>12VDC</p> <p>J08-CDE-1</p> <p>NO:50A NC:30A</p> <p>1c</p> <p>Diode</p> <p>-</p> <p>J08-CDE-1</p>	<p>24VDC</p> <p>J08-CDE-2</p> <p>NO:20A NC:15A</p> <p>1c</p> <p>Diode</p> <p>-</p>

JBCRD POWER RELAY

(RoHS 2011/65/EU & ELV 2000/53/EC 対応品)

パワーリレー 200A-24VDC		Rated Voltage	12VDC	24VDC
		JBC No	J09-ARE-1	J09-ARE-2
		Rated lode	200A(Continuous)	200A(Continuous)
		Contact circuit configuration	1a	1a
		Coil surge measures	Resistance	Resistance
		Coil resistance	30Ω	120Ω
		Excitation current	400mA	200mA
		Operating temperature	-40~75°C	-40~75°C
		Rated Voltage	12VDC	24VDC
		JBC No	J09-ADE-1	J09-ADE-2
Rated lode	200A(Continuous)	200A(Continuous)		
Contact circuit configuration	1a	1a		
Coil surge measures	Diode	Diode		
Coil resistance	30Ω	120Ω		
Excitation current	400mA	200mA		
Operating temperature	-40~75°C	-40~75°C		
Weight :	≒330g			